


## Specification Sheet

Part Number: 170-03087



Braided Sleeving, Split Wrap, 1.5" Dia, PET, Orange, 75 ft/bulk reel

**Article Number**

170-03087

**Type**

BSPSW1123B

**Color**

Orange (OG)

### Features & Benefits

- Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.
- Unique construction retains shape and rigidity throughout unrolling.
- Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.

**Quantity Per**

reel

### Product Description

A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

<b>Short Description</b>	Braided Sleeving, Split Wrap, 1.5" Dia, PET, Orange, 75 ft/bulk reel
<b>Global Part Name</b>	BSPSW1123B-PET-OG
<b>Length L (Imperial)</b>	75.0
<b>Length L (Metric)</b>	22.9
<b>Bundle Diameter Min (Imperial)</b>	0.1
<b>Bundle Diameter Min (Metric)</b>	2.54
<b>Bundle Diameter Max (Imperial)</b>	1.5
<b>Bundle Diameter Max (Metric)</b>	38.1
<b>Diameter D (imperial)</b>	2.0
<b>Diameter D (metric)</b>	50.8
<b>Nominal Diameter (Imperial)</b>	1-1/2
<b>Nominal Diameter (Metric)</b>	38.1
<b>Wall Thickness WT (Imperial)</b>	0.038
<b>Wall Thickness WT (Metric)</b>	0.97
<b>Material</b>	Polyester (PET)

**Material Shortcut**

PET

**Flammability**

UL 94 V0

**Halogen free**

Yes

**Operating Temperature (Metric)**

-94°F to +257°F (-70°C to +120°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**UL Recognized (US)**

Yes

**UL Recognized (US and Canada)**

Yes

**Package Quantity(Imperial)**

75

**Package Quantity (Metric)**

22.86

**Customs Number**

3926909987

**Weight (Metric)**

0.95

**Weight (Imperial)**

2.1