



- 注:
1. 適用製品規格: 108-5302
  2. 適用コネクタ型番  
タブ・コネクタ: 175150-FJC20-16AWG  
175149-FJC26-22AWG
  3. 嵌合相手側製品型番  
プラグ・ハウジング: 176279-C1  
リセ・コネクタ: 175152-FJC20-16AWG  
175151-FJC26-22AWG
  4. 取扱説明書: IS-503J

- NOTES:
1. PRODUCT SPEC.: 108-5302
  2. APPLICABLE CONTACT P/N  
TAB CONTACT: 175150-FJC20-16AWG  
: 175149-FJC26-22AWG
  3. MATING CONN. P/N  
PLUG HSG: 176279-C1  
REC CONTACT: 175152-FJC20-16AWG  
175151-FJC26-22AWG
  4. INSTRUCTION SHEET: IS-503J

断面 "A-A"  
(SECT)

回路番号  
(CIRCUIT No.)

黒 (BLACK)	15	176290-9
青 (BLUE)	↑	-5
黄 (YELLOW)	↓	-4
赤 (RED)	↓	-2
自然色 (NATURAL)	15	176290-1
ハウジング色調 (HOUSING COLOR)	種数 (Pos.)	型番 (P/N)

**AMP**

日本エンプラ株式会社  
Tokyo, Japan

名称 (NAME) AMPユニバーサル・パワー・コネクタ 15極  
3.95mmピッチ キーロック・ハウジング (3列タイプ)  
AMP UNIVERSAL POWER CONN. 3.95mm PITCH CAP HOUSING 15 Pos (3PL ROW)

LTR	変更 (REVISION RECORD)	DR	CHK	DATE
A	変更 J-12948 Y.N.	11/23 '89		
0	作成 J-12204 H.S.	11/23 '89		

完全電線耐燃性 (UL94V-0)	完全電線耐燃性 (UL94V-0)	完全電線耐燃性 (UL94V-0)
材料 (MATERIAL)	材料 (MATERIAL)	材料 (MATERIAL)
S/B NYLON (UL94V-0)	S/B NYLON (UL94V-0)	S/B NYLON (UL94V-0)
DR. M. SHINDO	DR. M. SHINDO	DR. M. SHINDO
CHK. N. YOSHIDA	CHK. N. YOSHIDA	CHK. N. YOSHIDA
Y. FUJITA	Y. FUJITA	Y. FUJITA
11/28 '89	11/28 '89	11/28 '89
APP. N. ONOUE	APP. N. ONOUE	APP. N. ONOUE
11/23 '89	11/23 '89	11/23 '89

公差 (TOLERANCE)	公差 (TOLERANCE)	公差 (TOLERANCE)
±0.2	±0.25	±0.3
寸法 (DIMENSIONS)	寸法 (DIMENSIONS)	寸法 (DIMENSIONS)
A3	J	C-176290
尺 (SCALE)	尺 (SCALE)	尺 (SCALE)
REV. A	REV. A	REV. A
SHEET 1 OF 1	SHEET 1 OF 1	SHEET 1 OF 1